

EPSON®

Projectors, Displays & Document Cameras

2024 Line Guide



Optional camera sold separately.

	Budget-Friendly Classroom Projectors			Basic Projectors for Small and Medium Rooms
Note: Highlighted boxes indicate step-ups between models within a series.				
Epson Model	PowerLite® E20	PowerLite X49	PowerLite W49	PowerLite 1288
Product Code	V11H981020	V11H982020	V11H983020	V11H978120
Replacement Lamp Code	V13H010L97	V13H010L97	V13H010L97	V13H010L97
Previous Epson Model	PowerLite S39	PowerLite X39	PowerLite W39	PowerLite 1286
Limited Warranty	2-year	2-year	2-year	2-year
Basics				
Color Brightness (Color Lumens)*	3,400	3,600	3,800	4,000
White Brightness (White Lumens)*	3,400	3,600	3,800	4,000
Light Source	Lamp	Lamp	Lamp	Lamp
Light Source Life Cycle up to (Normal/Medium/Eco [Hours])†	6,000/-/12,000	6,000/-/12,000	8,000/10,000/17,000	5,500/-/12,000
Native Resolution**	XGA	XGA	WXGA	1080p
Resolution on Screen	XGA	XGA	WXGA	1080p
Ultra Wide Aspect Ratios	–	–	–	–
Weight	5.9 lb	5.9 lb	5.9 lb	6.8 lb
Dimensions (Inches)††	11.8 x 9.8 x 3.6	11.8 x 9.8 x 3.6	11.8 x 9.8 x 3.6	12.1 x 11.5 x 4.1
Dynamic Contrast Ratio (up to)	15,000:1	16,000:1	16,000:1	16,000:1
Throw Ratio	1.44 Wide, 1.95 Tele	1.48 Wide, 1.77 Tele	1.30 Wide, 1.56 Tele	1.32 Wide, 2.14 Tele
Zoom Lens (Ratio)	1.35x Digital	1.2x Optical	1.2x Optical	1.6x Optical
Power Consumption	345 W	345 W	345 W	345 W
Value-Added Features				
Built-In Speaker	5 W	5 W	5 W	16 W
Closed Captioning	YES	YES	YES	YES
A/V Mute	Digital/Manual	Digital/Manual	Digital/Manual	Digital/Manual
Split Screen***	YES	YES	YES	YES
Edge Blending	–	–	–	–
Scheduling Function	–	–	–	–
Easy Connectivity and Setup				
Epson iProjection™ Suite (Moderator, Multi-PC, Device Management)****	–	YES	YES	YES
Signage Content Playback and Management Software*****	–	–	–	–
Miracast®	–	–	–	YES
Quick Corner Adjustments	YES	YES	YES	YES
Screen Fit	–	–	–	–
Keystone (Horizontal/Vertical)	Easy-Slide/Manual	Easy-Slide/Auto	Easy-Slide/Auto	Easy-Slide/Auto
LAN Networking and Control				
Wired	–	RJ-45 (Content over IP)	RJ-45 (Content over IP)	–
Wireless*****	–	Optional (802.11 b/g/n)	Optional (802.11 b/g/n)	Included (802.11 b/g/n), QR Code Quick Connect
Compatible Control Systems	–	Crestron®, AMX®, Extron®, Control4®	Crestron, AMX, Extron, Control4	–
Connections				
HDMI®	HDMI x 1	HDMI x 1	HDMI x 2	HDMI x 2
Analog Connections	VGA x 2, Composite x 1	VGA x 2, Composite x 1	VGA x 2, Composite x 1	VGA x 1, Composite x 1
Audio In	RCA (L & R) x 1, Mini Stereo x 2	RCA (L & R) x 1, Mini Stereo x 2	RCA (L & R) x 1, Mini Stereo x 2	RCA x 1
Variable Audio Out	Mini Stereo x 1	Mini Stereo x 1	Mini Stereo x 1	–
USB 2.0 Connectors	Type-B x 1	Type-B x 1, Type-A x 1	Type-B x 1, Type-A x 1	–
HDBaseT®	–	–	–	–
Monitor Out	D-Sub (15-Pin) x 1	D-Sub (15-Pin) x 1	D-Sub (15-Pin) x 1	–
Serial Control	RS-232c x 1	RS-232c x 1	RS-232c x 1	–
Recommended Accessory 1	Soft Carrying Case (ELPKS70)	Wireless LAN Module (ELPAP11)	Wireless LAN Module (ELPAP11)	ES3000 Screen
Recommended Accessory 2	DC-13 Document Camera	DC-13 Document Camera	DC-13 Document Camera	Carrying Case

*Color brightness (color light output) and white brightness (white light output) will vary depending on usage conditions. Color light output measured in accordance with IDMS 15.4; white light output measured in accordance with ISO 21118. **WUXGA (1920 x 1200), WXGA (1280 x 800), XGA (1024 x 768), SVGA (800 x 600). ***Split Screen feature requires remote control. Consult your user manual for input combinations. ****For wireless functionality, including via the Epson iProjection app, the projector must be configured on a network, either through the Ethernet port on the projector (check model specifications for availability) or via a wireless connection. Check your owner's manual to determine if a wireless LAN module must be purchased separately to enable a wireless connection. Not all Epson projectors are able to be networked. The Epson iProjection app does not support all files and formats. See www.epson.com for details. *****Internet connection required for download. Data usage fees may apply. *****Wi-Fi CERTIFIED™; level of performance subject to the range of the router being used.

Meeting Room and Large Room Projectors – 2000 Series

Advanced Networking Classroom Projectors – Standard Throw

				
PowerLite 2250U	PowerLite 118	PowerLite 119W	PowerLite 982W	PowerLite 992F
V11H871020	V11HA03020	V11H985020	V11H987020	V11H988020
V13H010L95	V13H010L97	V13H010L97	V13H010L97	V13H010L97
PowerLite 1980WU	PowerLite 108	PowerLite 109W	PowerLite 980W	PowerLite 990U
2-year	2-year	2-year	2-year	2-year
5,000	3,800	4,000	4,200	4,000
5,000	3,800	4,000	4,200	4,000
Lamp	Lamp	Lamp	Lamp	Lamp
5,000/10,000	8,000/10,000/17,000	8,000/10,000/17,000	6,500/10,000/17,000	6,500/10,000/17,000
WUXGA	XGA	WXGA	WXGA	1080p
WUXGA	XGA	WXGA	WXGA	1080p
–	–	–	–	–
10.2 lb	6.2 lb	6.2 lb	6.8 lb	6.8 lb
14.9 x 11.5 x 5.0	11.8 x 10.2 x 3.6	11.8 x 10.2 x 3.6	12.2 x 11.5 x 4.1	12.2 x 11.5 x 4.1
15,000:1	16,000:1	16,000:1	16,000:1	16,000:1
1.38 Wide, 2.28 Tele	1.48 Wide, 1.77 Tele	1.38 Wide, 1.56 Tele	1.38 Wide, 2.24 Tele	1.32 Wide, 2.14 Tele
1.0x – 1.6x Optical	1.2x Optical	1.2x Optical	1.6x Optical	1.6x Optical
429 W	345 W	345 W	345 W	345 W
16 W	16 W	16 W	16 W	16 W
YES	YES	YES	YES	YES
Digital/Manual	Digital/Manual	Digital/Manual	Digital/Manual	Digital/Manual
YES	YES	YES	YES	YES
–	–	–	–	–
YES	–	–	–	–
YES	YES	YES	YES	YES
–	–	–	–	YES
YES	YES	YES	YES	YES
YES	–	–	–	–
Auto/Auto	Easy-Slide/Auto	Easy-Slide/Auto	Easy-Slide/Auto	Easy-Slide/Auto
RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)
Optional (802.11 b/g/n)	Optional (802.11 b/g/n)	Optional (802.11 b/g/n)	Optional (802.11 b/g/n)	Included (802.11 b/g/n)
Crestron, AMX, Extron, Control4	Crestron, AMX, Extron, Control4	Crestron, AMX, Extron, Control4	Crestron, AMX, Extron, Control4	Crestron, AMX, Extron, Control4
HDMI x 2 (Includes MHL® x 1)	HDMI x 2	HDMI x 2	HDMI x 2	HDMI x 2
VGA x 2, Composite Video	VGA x 2, Composite x 1	VGA x 2, Composite x 1	VGA x 2, Composite x 1	VGA x 2, Composite x 1
RCA (L & R) x 1, Mini Stereo x 2	RCA (L & R) x 1, Mini Stereo x 2	RCA (L & R) x 1, Mini Stereo x 2	RCA (L & R) x 1, Mini Stereo x 2	RCA (L & R) x 1, Mini Stereo x 2
Mini Stereo x 1	Mini Stereo x 1	Mini Stereo x 1	Mini Stereo x 1	Mini Stereo x 1
Type-B x 1, Type-A x 1	Type-B x 1, Type-A x 1	Type-B x 1, Type-A x 1	Type-B x 1, Type-A x 1	Type-B x 1, Type-A x 1
–	–	–	–	–
Mini D-Sub (15-Pin) x 1	D-Sub (15-Pin) x 1	D-Sub (15-Pin) x 1	D-Sub (15-Pin) x 1	D-Sub (15-Pin) x 1
RS-232c x 1	RS-232c x 1	RS-232c x 1	RS-232c x 1	RS-232c x 1
Universal Projector Mount (ELPMBPJG)	Wireless LAN Module (ELPAP11)	Wireless LAN Module (ELPAP11)	Wireless LAN Module (ELPAP11)	Universal Mount (ELPMBPJG)
Wireless LAN Module (ELPAP11)	DC-21 Document Camera	DC-21 Document Camera	DC-21 Document Camera	DC-21 Document Camera

†Lamp light source life will vary depending upon mode selected, environmental conditions and usage. Lamp brightness decreases over time. Lamps come with a 90-day limited warranty.

‡Dimensions including feet and standard lens.

Advanced Networking Classroom Laser Projectors – Short Throw		Advanced Networking Projectors – Ultra Short Throw		Advanced Networking Laser	
					
PowerLite L210SF	PowerLite L210SW	PowerLite 685W	PowerLite 760W		
V11HA75020	V11HA76020	V11H744520	V11HA81020		
–	–	V13H010L91	Laser		
–	PowerLite L200W	PowerLite 585W	PowerLite 725W		
3-year [‡]	3-year [‡]	2-year	3-year [‡]		
4,000	4,000	3,500	4,100		
4,000	4,000	3,500	4,100		
Laser	Laser	Lamp	Laser		
20,000/-/30,000 [‡]	20,000/-/30,000 [‡]	5,000/-/10,000	20,000/-/30,000 [‡]		
1080p	WXGA	WXGA	WXGA		
1080p	WXGA	WXGA	WXGA		
21:9, 16:6	–	–	–		
9.9 lb	9.9 lb	12.6 lb	12.5 lb		
12.8 x 3.6 x 13.3	12.8 x 3.6 x 13.3	14.5 x 15.8 x 7.4	14.1 x 15.6 x 5.25		
5,000,000:1	5,000,000:1	14,000:1	5,000,000:1		
0.45 Wide, 0.61 Tele	0.48 Wide, 0.65 Tele	0.28 Wide, 0.37 Tele	0.28 Wide, 0.37 Tele		
1.35x Digital	1.35x Digital	1.35x Digital	1.35x Digital		
265 W	265 W	373 W	267 W		
16 W	16 W	16 W	16 W		
YES	YES	YES	YES		
Digital	Digital	Digital	Digital		
YES	YES	YES	YES		
–	–	–	–		
–	–	–	–		
YES	YES	YES	YES		
–	–	–	–		
YES	YES	–	YES		
YES	YES	YES	YES		
–	–	–	–		
Manual/Manual	Manual/Manual	Manual/Manual	Manual/Manual		
RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)		
Included (802.11 a/b/g/n/ac); 2.4/5 GHz	Included (802.11 a/b/g/n/ac); 2.4/5 GHz	Optional (802.11 b/g/n)	Included (802.11 a/b/g/n/ac); 5 GHz		
Crestron, AMX, Extron, Art-Net, PJLink	Crestron, AMX, Extron, Art-Net, PJLink	Crestron, AMX, Extron, Control4, PJLink	Crestron, AMX, Extron, Control4, PJLink		
HDMI x 2	HDMI x 2	HDMI x 3 (Includes MHL x 1)	HDMI x 3		
VGA x 2, Composite Video	VGA x 2, Composite Video	VGA x 2, Composite Video	VGA x 2, Composite Video		
RCA (L & R) x 1, Mini Stereo x 2, Mic In	RCA (L & R) x 1, Mini Stereo x 2, Mic In	Mini Stereo x 3	Mini Stereo x 3, Mic In		
Mini Stereo x 1	Mini Stereo x 1	Mini Stereo x 1	Mini Stereo x 1		
Type-B x 1, Type-A with 2 Amp Power x 1	Type-B x 1, Type-A with 2 Amp Power x 1	Type-B x 1, Type-A x 1	Type-B x 1, Type-A x 2		
–	–	–	–		
Mini D-Sub (15-Pin) x 1	Mini D-Sub (15-Pin) x 1	Mini D-Sub (15-Pin) x 1	Mini D-Sub (15-Pin) x 1		
RS-232c x 1	RS-232c x 1	RS-232c x 1	RS-232c x 1		
Short Throw Wall Mount (ELPMB64)	Short Throw Wall Mount (ELPMB64)	Ultra Short Throw Wall Mount (ELPMB62)	Ultra Short Throw Wall Mount (ELPMB62)		
PowerLite Pilot™ 3 Connection and Control Box (ELPCB03)	PowerLite Pilot 3 Connection and Control Box (ELPCB03)	PowerLite Pilot 3 Connection and Control Box (ELPCB03)	DC-21 Document Camera		







[‡]20,000 hours is the estimated life when the projector is used in Normal Mode in an ordinary environment, 30,000 hours in Eco Mode. Actual hours may vary depending on mode and usage environment. The projector has a limited warranty of 3 years or 20,000 hours, whichever comes first. ^Δ5-year with product registration.

Projectors for Classrooms and Digital Signage – Ultra Short Throw		Ultra Mobile Projectors – 1700 Series, Extra Thin and Light	
			
PowerLite 770F / PowerLite 775F	PowerLite 800F / PowerLite 805F	PowerLite 1785W	PowerLite 1795F
V11HA79020 / V11HA83120	V11H923520 / V11H923620	V11H793020	V11H796020
Laser	Laser	V13H010L94	V13H010L94
PowerLite 750F / PowerLite 755F	PowerLite 700U	PowerLite 1776W	–
3-year ^d	3-year ^d	2-year	2-year
4,100	5,000	3,200	3,200
4,100	5,000	3,200	3,200
Laser	Laser	Lamp	Lamp
20,000/-/30,000 [†]	20,000/-/30,000 [†]	4,000/-/7,000	4,000/-/7,000
1080p	1366 x 768 with Panel Shift	WXGA	1080p
1080p	1080p	WXGA	1080p
21:9, 16:6	21:9, 16:6	–	–
12.5 lb	21.4 lb	4.0 lb	4.0 lb
14.1 x 15.6 x 5.25	18.1 x 17.7 x 9.0	11.5 x 8.4 x 2.1	11.5 x 8.4 x 2.1
Dynamic 5,000,000:1, Native 1,400:1	Dynamic 5,000,000:1, Native 1,440:1	10,000:1	10,000:1
0.26 Wide, 0.36 Tele	0.27 Wide, 0.37 Tele	1.04 Wide, 1.26 Tele	1.02 Wide, 1.23 Tele
1.35x Digital	1.35x Digital	1.2x Optical	1.2x Optical
267 W	381 W	309 W	309 W
16 W	8 W x 2	1 W	1 W
YES	YES	YES	YES
Digital	Digital	Digital/Manual	Digital/Manual
YES	YES	YES	YES
YES	YES	–	–
YES	YES	–	–
YES	YES	YES	YES
YES	YES	YES	YES
–	–	YES	YES
Manual/Manual	Manual/Manual	Auto/Auto	Auto/Auto
RJ-45 (Content over IP)	RJ-45 (Content over IP)	–	–
Included (802.11 b/g/n), 2.4 GHz; (802.11 a/n/ac), 5 GHz	Optional (802.11 b/g/n), 2.4 GHz; (802.11 a/n/ac), 5 GHz	Included (802.11 b/g/n)	Included (802.11 b/g/n)
Crestron, AMX, Extron, PJLink, Art-Net, Control4	Crestron, AMX, Extron, PJLink, Art-Net, Control4	–	–
HDMI x 3	HDMI x 3	HDMI x 1	HDMI x 1
VGA x 2, Composite Video	VGA x 2, Composite Video	VGA x 1, Composite Video	VGA x 1, Composite Video
Mini Stereo x 3	Mini Stereo x 3	Mini Stereo x 1	Mini Stereo x 1
Mini Stereo x 1	Mini Stereo x 1	–	–
Type-B x 1, Type-A with 2 Amp Power x 1	Type-B x 1, Type-A x 2	Type-B x 1, Type-A x 1	Type-B x 1, Type-A x 1
–	YES	–	–
Mini D-Sub (15-Pin) x 1	Mini D-Sub (15-Pin) x 1, HDMI Out	–	–
RS-232c x 1	RS-232c x 1	–	–
Ultra Short Throw Wall Mount (ELPMB62)	Ultra Short Throw Wall Mount (ELPMB62)	ES3000 Screen	ES3000 Screen
DC-21 Document Camera	Wireless LAN Module	DC-21 Document Camera	DC-21 Document Camera

^d5-year with product registration.

PowerLite Standard Throw Laser Projectors

PowerLite L Series Laser Projectors

<p>Note: Highlighted boxes indicate step-ups between models within a series.</p>							
	Epson Model	PowerLite L210W	PowerLite L260F / PowerLite L265F	PowerLite L520W	PowerLite L520U	PowerLite L530U	PowerLite L630U
	Product Code	V11HA70020	V11HA69020 / V11HA72120	V11HA31020	V11HA30020	V11HA27020	V11HA26020
	Previous Epson Model	PowerLite L200W	PowerLite L250F	PowerLite L500W	PowerLite L400U	PowerLite L510U	PowerLite L610U
	Limited Warranty	3-year ^Δ	3-year ^Δ	3-year	3-year	3-year	3-year
Basics							
Color Brightness (Color Lumens)*	4,500	4,600	5,200	5,200	5,200	6,200	
White Brightness (White Lumens)*	4,500	4,600	5,200	5,200	5,200	6,200	
Light Source	Laser	Laser	Laser	Laser	Laser	Laser	
Light Source Life up to (Normal/Extended [Hours])†	20,000/30,000 [‡]	20,000/30,000 [‡]	20,000/30,000 [‡]	20,000/30,000 [‡]	20,000/30,000 [‡]	20,000/30,000 [‡]	
Native Resolution**	WXGA	1080p	WXGA	WUXGA	WUXGA	WUXGA	
Resolution on Screen	WXGA	1080p	WXGA	WUXGA	WUXGA	WUXGA	
Ultra Wide Aspect Ratios	–	21:9, 16:6	–	21:9, 16:6	21:9, 16:6	21:9, 16:6	
Weight	9.5 lb	9.5 lb	16.1 lb	17.0 lb	18.1 lb	18.5 lb	
Dimensions (Inches)††	19.1 x 14.4 x 6.9	19.1 x 14.4 x 6.9	17.32 x 11.97 x 4.80	17.32 x 11.97 x 4.80	17.32 x 11.97 x 4.80	17.32 x 11.97 x 4.80	
Dynamic Contrast Ratio (up to)	5,000,000:1	5,000,000:1	5,000,000:1	5,000,000:1	5,000,000:1	5,000,000:1	
Throw Ratio	1.41 Wide, 2.26 Tele	1.32 Wide, 2.12 Tele	1.38 Wide, 2.24 Tele	1.35 Wide, 2.20 Tele	1.35 Wide, 2.20 Tele	1.35 Wide, 2.20 Tele	
Zoom Lens (Ratio)	1.0x – 1.6x Optical	1.0x – 1.6x Optical	1.00x – 1.6x Optical	1.00x – 1.6x Optical	1.00x – 1.6x Optical	1.00x – 1.6x Optical	
Power Consumption	272 W	272 W	301 W	301 W	301 W	358 W	
Value-Added Features							
Built-In Speaker	16 W	16 W	10 W	10 W	10 W	10 W	
Closed Captioning	YES	YES	YES	YES	YES	YES	
A/V Mute	Digital/Manual	Digital/Manual	Digital	Digital	Digital	Digital	
Split Screen***	YES	YES	YES	YES	YES	YES	
Edge Blending	–	YES	–	YES	YES	YES	
Camera	–	–	–	–	–	–	
Scheduling Function	YES	YES	YES	YES	YES	YES	
Easy Connectivity and Setup							
Epson iProjection Suite (Moderator, Multi-PC, Device Management)****	YES	YES	YES	YES	YES	YES	
Signage Content Playback and Management Software*****	–	YES	YES	YES	YES	YES	
Miracast	YES	YES	–	Optional	YES	YES	
Quick Corner Adjustments	YES	YES	YES	YES	YES	YES	
Keystone (Horizontal/Vertical)	Easy-Slide/Auto	Easy-Slide/Auto	Manual/Manual	Manual/Manual	Manual/Manual	Manual/Manual	
Lens Shift (Vertical and Horizontal)	–	–	–	–	YES	YES	
LAN Networking and Control							
Wired	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)	
Wireless*****	Included (802.11 b/g/n/a/ac); 2.4 GHz and 5 GHz	Included (802.11 b/g/n/a/ac); 2.4 GHz and 5 GHz	Optional (802.11 b/g/n)	Optional (802.11 b/g/n)	Included (802.11 b/g/n/a/ac), 2.4 GHz and 5 GHz	Included (802.11 b/g/n/a/ac), 2.4 GHz and 5 GHz	
Compatible Control Systems	Crestron, AMX, Extron, PJLink, Control4	Crestron, AMX, Extron, PJLink, Art-Net, Control4	Crestron, AMX, PJLink, Control4	Crestron, AMX, PJLink, Control4	Crestron, AMX, PJLink, Control4	Crestron, AMX, PJLink, Control4	
Connections							
HDMI	HDMI x 2	HDMI x 2	HDMI x 2	HDMI x 2	HDMI x 2, HDMI Out x 1	HDMI x 2, HDMI Out x 1	
Analog Connections	VGA x 2, Composite Video	VGA x 2, Composite Video	VGA x 2	VGA x 2	VGA x 2	VGA x 2	
Audio In	RCA (L & R) x 1, Mini Stereo x 2	RCA (L & R) x 1, Mini Stereo x 2	Mini Stereo x 2	Mini Stereo x 2	Mini Stereo x 2	Mini Stereo x 2	
Variable Audio Out	Mini Stereo x 1	Mini Stereo x 1	Mini Stereo x 1	Mini Stereo x 1	Mini Stereo x 1	Mini Stereo x 1	
USB 2.0 Connectors	Type-A with 5V/2A Power Supply, Type-B	Type-A with 5V/2A Power Supply, Type-B	Type-B x 1, Type-A x 1	Type-B x 1, Type-A x 1	Type-B x 1, Type-A x 1	Type-B x 1, Type-A x 1	
DVI-D	–	–	–	–	–	–	
HDBaseT	–	–	YES	YES	YES	YES	
SDI	–	–	–	–	–	–	
Monitor Out	Mini D-Sub (15-Pin) x 1	Mini D-Sub (15-Pin) x 1	Mini D-Sub (15-Pin) x 1	Mini D-Sub (15-Pin) x 1	Mini D-Sub (15-Pin) x 1	Mini D-Sub (15-Pin) x 1	
Serial Control	RS-232c x 1	RS-232c x 1	RS-232c x 1	RS-232c x 1	RS-232c x 1	RS-232c x 1	
Recommended Accessory 1	Ceiling Mount (ELPMB60W)	Ceiling Mount (ELPMB60W)	Projector Ceiling Mount (ELPMBPJG / ELPMBPRH)	Projector Ceiling Mount (ELPMBPJG / ELPMBPRH)	Projector Ceiling Mount (ELPMBPJG / ELPMBPRH)	Projector Ceiling Mount (ELPMBPJG / ELPMBPRH)	
Recommended Accessory 2	DC-21 Document Camera	DC-21 Document Camera	Wireless LAN Module (ELPAP11)	Wireless LAN Module (ELPAP11)	Wireless LAN Module (ELPAP11)	Wireless LAN Module (ELPAP11)	

*Color brightness (color light output) and white brightness (white light output) will vary depending on usage conditions. Color light output measured in accordance with IDMS 15.4; white light output measured in accordance with ISO 21118. **WUXGA (1920 x 1200), WXGA (1280 x 800), XGA (1024 x 768), SVGA (800 x 600). ***Split Screen feature requires remote control. Consult your user manual for input combinations. ****For wireless functionality, including via the Epson iProjection app, the projector must be configured on a network, either through the Ethernet port on the projector (check model specifications for availability) or via a wireless connection. Check your owner's manual to determine if a wireless LAN module must be purchased separately to enable a wireless connection. Not all Epson projectors are able to be networked. The Epson iProjection app does not support all files and formats. See www.epson.com for details. *****Internet connection required for download. Data usage fees may apply. *****Wi-Fi CERTIFIED; level of performance subject to the range of the router being used.

Projectors for Meeting Rooms and Large Rooms

						
PowerLite L730U / PowerLite L735U	PowerLite L630SU / PowerLite L635SU	PowerLite L570U	PowerLite L770U / PowerLite L775U	EB-PU1006W	EB-PU1007W / EB-PU1007B	EB-PU1008W / EB-PU1008B
V11HA25020 / V11HA25120	V11HA29020 / V11HA29120	V11HA98020	V11HA96020 / V11HA96120	V11HA35920	V11HA34920 / V11HA34820	V11HA33920 / V11HA33820
–	–	–	–	Pro L1060UNL	Pro L1070UNL	Pro L1490UNL
3-year	3-year	3-year	3-year	3-year	3-year	3-year
7,000	6,000	5,200	7,000	6,000	7,000	8,500
7,000	6,000	5,200	7,000	6,000	7,000	8,500
Laser	Laser	Laser	Laser	Laser	Laser	Laser
20,000/30,000 ^{†††}	20,000/30,000 ^{†††}	20,000/30,000 ^{†††}	20,000/30,000 ^{†††}	20,000/30,000 [†]	20,000/30,000 [†]	20,000/30,000 [†]
WUXGA	WUXGA	WUXGA with 4K Enhancement ^{††}	WUXGA with 4K Enhancement ^{††}	WUXGA with 4K Enhancement ^{††}	WUXGA with 4K Enhancement ^{††}	WUXGA with 4K Enhancement ^{††}
WUXGA	WUXGA	1920 x 1200 x 2	1920 x 1200 x 2	1920 x 1200 x 2	1920 x 1200 x 2	1920 x 1200 x 2
21:9, 16:6	21:9, 16:6	21:9, 16:6	21:9, 16:6	21:9	21:9	21:9
18.5 lb	18.5 lb	18.7 lb	19.1 lb	34.2 lb	36.2 lb	36.2 lb
17.32 x 11.97 x 4.80	17.32 x 11.97 x 4.80	17.32 x 11.97 x 4.80	17.32 x 11.97 x 4.80	21.5 x 17.2 x 6.5	21.5 x 17.2 x 6.5	21.5 x 17.2 x 6.5
5,000,000:1	5,000,000:1	5,000,000:1	5,000,000:1	5,000,000:1	5,000,000:1	5,000,000:1
1.35 Wide, 2.20 Tele	0.80 Wide, 1.07 Tele (Digital)	1.35 Wide, 2.20 Tele	1.35 Wide, 2.20 Tele	See Page 10 for Optional Lenses		
1.00x – 1.6x Optical	1.00x – 1.35x Digital	1.00x – 1.6x Optical	1.00x – 1.6x Optical			
358 W	358 W	323 W	382 W	384 W	448 W	559 W
10 W	10 W	10 W	10 W	–	–	–
YES	YES	–	–	–	–	–
Digital	Digital	Digital	Digital	Digital	Digital	Digital
YES	YES	YES	YES	YES	YES	YES
YES	YES	YES	YES	YES	YES	YES
–	–	Optional (ELPEC01)	Optional (ELPEC01)	Optional (ELPEC01)	Optional (ELPEC01)	Optional (ELPEC01)
YES	YES	YES	YES	YES	YES	YES
YES	YES	YES	YES	YES	YES	YES
YES	YES	–	–	–	–	–
YES	YES	YES	YES	YES	YES	YES
Manual/Manual	Manual/Manual	Manual/Manual	Manual/Manual	Manual/Manual	Manual/Manual	Manual/Manual
YES	YES	YES	YES	Powered with Lens Memory	Powered with Lens Memory	Powered with Lens Memory
RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)
Included (802.11 b/g/n/a/ac), 2.4 GHz and 5 GHz	Included (802.11 b/g/n/a/ac), 2.4 GHz and 5 GHz	Optional (802.11 b/g/n)	Optional (802.11 b/g/n)	Optional (802.11 b/g/n)	Optional (802.11 b/g/n)	Optional (802.11 b/g/n)
Crestron, AMX, PJLink, Control4	Crestron, AMX, PJLink, Control4	Crestron, AMX, PJLink, Control4	Crestron, AMX, PJLink, Control4	Crestron, AMX, Extron, Art-Net	Crestron, AMX, Extron, Art-Net	Crestron, AMX, Extron, Art-Net
HDMI x 2, HDMI Out x 1	HDMI x 2, HDMI Out x 1	HDMI x 2, HDMI Out x 1	HDMI x 2, HDMI Out x 1	HDMI x 1 (HDCP 2.2)	HDMI x 1 (HDCP 2.2)	HDMI x 1 (HDCP 2.2)
VGA x 2	VGA x 2	–	–	VGA x 1	VGA x 1	VGA x 1
Mini Stereo x 2	Mini Stereo x 2	–	–	–	–	–
Mini Stereo x 1	Mini Stereo x 1	Mini Stereo x 1	Mini Stereo x 1	Mini Stereo x 1	Mini Stereo x 1	Mini Stereo x 1
Type-B x 1, Type-A x 1	Type-B x 1, Type-A x 1	Type-B x 1, Type-A x 1	Type-B x 1, Type-A x 1	Type-B x 1 (For Service, Clone), Type-A x 1 (For Wireless, FW Update, Clone)		
–	–	–	–	DVI-D x 1	DVI-D x 1	DVI-D x 1
YES	YES	YES	YES	HDBaseT x 1 (HDCP 2.2)	HDBaseT x 1 (HDCP 2.2)	HDBaseT x 1 (HDCP 2.2)
–	–	–	–	–	–	–
Mini D-Sub (15-Pin) x 1	Mini D-Sub (15-Pin) x 1	–	–	–	–	–
RS-232c x 1	RS-232c x 1	RS-232c x 1	RS-232c x 1	RS-232c x 1	RS-232c x 1	RS-232c x 1
Projector Ceiling Mount (ELPMBPJG / ELPMBPRH)	Projector Ceiling Mount (ELPMBPJG / ELPMBPRH)	Projector Ceiling Mount (ELPMBPJG / ELPMBPRH)	Projector Ceiling Mount (ELPMBPJG / ELPMBPRH)	Ceiling Mount (ELPMB67)	Ceiling Mount (ELPMB67)	Ceiling Mount (ELPMB67)
Wireless LAN Module (ELPAP11)	Wireless LAN Module (ELPAP11)	Wireless LAN Module (ELPAP11)	Wireless LAN Module (ELPAP11)	PixAlign™ Camera (ELPEC01)	PixAlign Camera (ELPEC01)	PixAlign Camera (ELPEC01)

[†]Lamp life will vary depending upon mode selected, environmental conditions and usage. Lamp brightness decreases over time. The lamp comes with a 90-day limited warranty.

^{††}Dimensions including feet and standard lens.

Δ5-year with product registration.

Large Venue Installation – Pro Series Laser Projectors with Optional Lenses

						
EB-PU2010W / EB-PU2010B	EB-PU2113W	EB-PU2213B	EB-PU2116W	EB-PU2216B	EB-PU2120W	EB-PU2220B
V11HA52920 / V11HA52820	V11HA65920	V11HA68820	V11HA64920	V11HA67820	V11HA63920	V11HA66820
–	Pro L1500UH	Pro L1505UH	Pro L1750U	Pro L1755U	Pro L20002U	Pro L20000U
3-year	3-year	3-year	3-year	3-year	3-year	3-year
10,000	13,000	13,000	16,000	16,000	20,000	20,000
10,000	13,000	13,000	16,000	16,000	20,000	20,000
Laser	Laser	Laser	Laser	Laser	Laser	Laser
20,000/30,000 [‡]	20,000/30,000 [‡]	20,000/30,000 [‡]	20,000/30,000 [‡]	20,000/30,000 [‡]	20,000/30,000 [‡]	20,000/30,000 [‡]
WUXGA with 4K Enhancement ^{‡‡}	WUXGA with 4K Enhancement ^{‡‡}	WUXGA with 4K Enhancement ^{‡‡}	WUXGA with 4K Enhancement ^{‡‡}	WUXGA with 4K Enhancement ^{‡‡}	WUXGA with 4K Enhancement ^{‡‡}	WUXGA with 4K Enhancement ^{‡‡}
1920 x 1200 x 2	1920 x 1200 x 2	1920 x 1200 x 2	1920 x 1200 x 2	1920 x 1200 x 2	1920 x 1200 x 2	1920 x 1200 x 2
21:9	21:9	21:9	21:9	21:9	21:9	21:9
37.5 lb	52.4 lb	52.2 lb	53.5 lb	53.5 lb	53.7 lb	53.7 lb
21.5 x 17.2 x 6.5	23.1 x 19.4 x 7.3	23.1 x 19.4 x 7.3	23.1 x 19.4 x 7.3	23.1 x 19.4 x 7.3	23.1 x 19.4 x 7.3	23.1 x 19.4 x 7.3
5,000,000:1	5,000,000:1	5,000,000:1	5,000,000:1	5,000,000:1	5,000,000:1	5,000,000:1
See Page 10 for Optional Lenses						
559 W	886 W	886 W	1,118 W	1,118 W	1,301 W	1,301 W
–	–	–	–	–	–	–
–	–	–	–	–	–	–
Digital	Digital	Mechanical Shutter	Digital	Mechanical Shutter	Digital	Mechanical Shutter
YES	YES	YES	YES	YES	YES	YES
YES	YES	YES	YES	YES	YES	YES
Optional (ELPEC01)	Optional (ELPEC01)	Optional (ELPEC01)	Optional (ELPEC01)	Optional (ELPEC01)	Optional (ELPEC01)	Optional (ELPEC01)
YES	YES	YES	YES	YES	YES	YES
YES	YES	YES	YES	YES	YES	YES
–	–	–	–	–	–	–
–	–	–	–	–	–	–
YES	YES	YES	YES	YES	YES	YES
Manual/Manual	Manual/Manual	Manual/Manual	Manual/Manual	Manual/Manual	Manual/Manual	Manual/Manual
Powered with Lens Memory	Powered with Lens Memory	Powered with Lens Memory	Powered with Lens Memory	Powered with Lens Memory	Powered with Lens Memory	Powered with Lens Memory
RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)
Optional (802.11 b/g/n)	Optional (802.11 b/g/n)	Optional (802.11 b/g/n)	Optional (802.11 b/g/n)	Optional (802.11 b/g/n)	Optional (802.11 b/g/n)	Optional (802.11 b/g/n)
Crestron, AMX, Extron, Art-Net	Crestron, AMX, Extron, Art-Net	Crestron, AMX, Extron, Art-Net	Crestron, AMX, Extron, Art-Net	Crestron, AMX, Extron, Art-Net	Crestron, AMX, Extron, Art-Net	Crestron, AMX, Extron, Art-Net
HDMI x 1 (HDCP 2.2)	HDMI x 1 (HDCP 2.2)	HDMI x 1 (HDCP 2.2)	HDMI x 1 (HDCP 2.2)	HDMI x 1 (HDCP 2.2)	HDMI x 1 (HDCP 2.2)	HDMI x 1 (HDCP 2.2)
VGA x 1	VGA x 1	VGA x 1	VGA x 1	VGA x 1	VGA x 1	VGA x 1
–	–	–	–	–	–	–
Mini Stereo x 1	Mini Stereo x 1	Mini Stereo x 1	Mini Stereo x 1	Mini Stereo x 1	Mini Stereo x 1	Mini Stereo x 1
Type-B x 1 (For Service, Clone), Type-A x 3 (For Wireless, FW Update, Clone, Camera)						
DVI-D x 1	DVI-D x 1	DVI-D x 1	DVI-D x 1	DVI-D x 1	DVI-D x 1	DVI-D x 1
HDBaseT x 1 (HDCP 2.2)	HDBaseT x 1 (HDCP 2.2)	HDBaseT x 1 (HDCP 2.2)	HDBaseT x 1 (HDCP 2.2)	HDBaseT x 1 (HDCP 2.2)	HDBaseT x 1 (HDCP 2.2)	HDBaseT x 1 (HDCP 2.2)
3G-SDI In/Out	–	3G-SDI In/Out	–	3G-SDI In/Out	–	3G-SDI In/Out
–	–	–	–	–	–	–
RS-232c x 1	RS-232c x 1	RS-232c x 1	RS-232c x 1	RS-232c x 1	RS-232c x 1	RS-232c x 1
Ceiling Mount (ELPMB67)	Ceiling Mount (ELPMB67)	Ceiling Mount (ELPMB67)	Ceiling Mount (ELPMB67)	Ceiling Mount (ELPMB67)	Ceiling Mount (ELPMB67)	Ceiling Mount (ELPMB67)
PixAlign Camera (ELPEC01)	PixAlign Camera (ELPEC01)	PixAlign Camera (ELPEC01)	PixAlign Camera (ELPEC01)	PixAlign Camera (ELPEC01)	PixAlign Camera (ELPEC01)	PixAlign Camera (ELPEC01)

[‡]20,000 hours is the estimated laser light source life when used in Normal Mode, 30,000 hours in Eco Mode. Actual hours may vary depending on mode and usage environment. The projector has a standard limited warranty of 3 years.
^{‡‡}4K Enhancement Technology shifts each pixel to surpass Full HD resolution on screen.

Large Venue Installation – Pro Series 4K Laser Projectors

	Large Venue Installation – Pro Series 4K Laser Projectors				
					
Pro L3000UNL / Pro L3000OUNL	EB-PQ2008W / EB-PQ2008B	EB-PQ2010W / EB-PQ2010B	EB-PQ2213B	EB-PQ2216W / EB-PQ2216B	EB-PQ2220B
V11H944920 / V11H944820	V11HB01920 / V11HB01820	V11HB02920 / V11HB02820	V11HB03820	V11HB04920 / V11HB04820	V11HB05820
–	–	–	–	–	–
3-years or 20,000 hours	3-year	3-year	3-year	3-year	3-year
30,000	8,000	10,000	13,000	16,000	20,000
30,000	8,000	10,000	13,000	16,000	20,000
Laser	Laser	Laser	Laser	Laser	Laser
20,000/30,000 ^{††}	20,000/30,000 [†]	20,000/30,000 [†]	20,000/30,000 [†]	20,000/30,000 [†]	20,000/30,000 [†]
WUXGA with 4K Enhancement ^{††}	1080p with 4K Crystal Motion	1080p with 4K Crystal Motion	1080p with 4K Crystal Motion	1080p with 4K Crystal Motion	1080p with 4K Crystal Motion
1920 x 1200 x 2	4K UHD (3840 x 2160)	4K UHD (3840 x 2160)	4K UHD (3840 x 2160)	4K UHD (3840 x 2160)	4K UHD (3840 x 2160)
–	21:9	21:9	21:9	21:9	21:9
140.7 lb	41.0 lb	41.4 lb	63.4 lb	64.3 lb	64.3 lb
31.1 x 28 x 11.4	21.5 x 17.2 x 6.5	21.5 x 17.2 x 6.5	23.1 x 19.4 x 7.3	23.1 x 19.4 x 7.3	23.1 x 19.4 x 7.3
5,000,000:1	5,000,000:1	5,000,000:1	5,000,000:1	5,000,000:1	5,000,000:1
Optional Lenses	See Page 10 for Optional Lenses				
2,325 W	522 W	640 W	951 W	1,114 W	1,431 W
–	–	–	–	–	–
–	–	–	–	–	–
Mechanical Shutter	Digital	Digital	Mechanical Shutter	Mechanical Shutter	Mechanical Shutter
YES	YES	YES	YES	YES	YES
YES	YES	YES	YES	YES	YES
Built-In	Optional (ELPEC01)	Optional (ELPEC01)	Optional (ELPEC01)	Optional (ELPEC01)	Optional (ELPEC01)
YES	YES	YES	YES	YES	YES
YES	YES	YES	YES	YES	YES
–	–	–	–	–	–
–	–	–	–	–	–
YES	YES	YES	YES	YES	YES
Manual/Manual	Manual/Manual	Manual/Manual	Manual/Manual	Manual/Manual	Manual/Manual
Powered with Lens Memory	Powered with Lens Memory	Powered with Lens Memory	Powered with Lens Memory	Powered with Lens Memory	Powered with Lens Memory
RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)
Optional (802.11 b/g/n)	Optional (802.11 b/g/n)	Optional (802.11 b/g/n)	Optional (802.11 b/g/n)	Optional (802.11 b/g/n)	Optional (802.11 b/g/n)
Crestron, AMX, Extron, Art-Net	Crestron, AMX, Extron, Art-Net	Crestron, AMX, Extron, Art-Net	Crestron, AMX, Extron, Art-Net	Crestron, AMX, Extron, Art-Net	Crestron, AMX, Extron, Art-Net
HDMI x 1 (HDCP 2.2)	HDMI 2 In/1 Out (HDCP 2.3)	HDMI 2 In/1 Out (HDCP 2.3)	HDMI 2 In/1 Out (HDCP 2.3)	HDMI 2 In/1 Out (HDCP 2.3)	HDMI 2 In/1 Out (HDCP 2.3)
VGA x 1, 5-BNC x 1	–	–	–	–	–
–	–	–	–	–	–
–	Mini Stereo x 1	Mini Stereo x 1	Mini Stereo x 1	Mini Stereo x 1	Mini Stereo x 1
Type-B x 1, Type-A x 1	Type-B x 1, Type-A x 1		Type-B x 1 (For Service, Clone), Type-A x 3 (For Wireless, FW Update, Clone, Camera)		
DVI-D x 1	–	–	–	–	–
HDBaseT x 1 (HDCP 2.2)	HDBaseT x 1 (HDCP 2.3)	HDBaseT x 1 (HDCP 2.3)	HDBaseT x 1 (HDCP 2.3)	HDBaseT x 1 (HDCP 2.3)	HDBaseT x 1 (HDCP 2.3)
3G-SDI	–	12G-SDI In/Out	12G-SDI In/Out	12G-SDI In/Out	12G-SDI In/Out
Mini D-Sub (15-Pin) x 1	–	–	–	–	–
RS-232c x 1	RS-232c x 1	RS-232c x 1	RS-232c x 1	RS-232c x 1	RS-232c x 1
Stacking Frame (ELPMB52)	Ceiling Mount (ELPMB67)	Ceiling Mount (ELPMB67)	Ceiling Mount (ELPMB67)	Ceiling Mount (ELPMB67)	Ceiling Mount (ELPMB67)
Handling Frame (ELPMB56)	PixAlign Camera (ELPEC01)	PixAlign Camera (ELPEC01)	PixAlign Camera (ELPEC01)	PixAlign Camera (ELPEC01)	PixAlign Camera (ELPEC01)

††20,000 hours is the estimated life when the projector is used in Normal Mode in an ordinary environment, 30,000 hours in Eco Mode. Actual hours may vary depending on mode and usage environment. The projector has a limited warranty of 3 years or 20,000 hours, whichever comes first.

Interactive Laser Displays – BrightLink® Series				Extreme Short Throw
				
BrightLink 760Wi	BrightLink 770Fi	BrightLink 1480Fi	BrightLink 1485Fi	PowerLite 810E / PowerLite 815E
V11HA80020	V11HA78020	V11H921520	V11H919520	V11HA99020 / V11HA99120
BrightLink 725Wi	BrightLink 735Fi	BrightLink Pro 1460Ui	BrightLink Pro 1470Ui	–
3-year ^Δ	3-year ^Δ	3-year ^Δ	3-year ^Δ	3-year ^Δ
4,100	4,100	5,000	5,000	5,000
4,100	4,100	5,000	5,000	5,000
Laser	Laser	Laser	Laser	Laser
20,000/30,000 ⁺⁺	20,000/30,000 ⁺⁺	20,000/30,000 ⁺⁺	20,000/30,000 ⁺⁺	20,000/30,000 ⁺⁺
WXGA	1080p	1366 x 768 with Panel Shift	1366 x 768 with Panel Shift	1080p with 4K Enhancement ⁺⁺
WXGA	1080p	1080p	1080p	1920 x 1080 x 2
–	21:9, 16:6	–	21:9, 16:6	21:9, 16:6
12.7 lb	12.7 lb	21.4 lb	21.4 lb	27.6 lb
14.1 x 15.6 x 5.25	14.1 x 15.6 x 5.25	18.1 x 14.3 x 8.3	18.1 x 14.3 x 8.3	27.4 x 13.5 x 5.7
5,000,000:1	5,000,000:1	5,000,000:1	5,000,000:1	5,000,000:1
0.28 Wide, 0.37 Tele	0.26 Wide, 0.36 Tele	0.27 Wide, 0.37 Tele	0.27 Wide, 0.37 Tele	0.16 Wide, 0.22 Tele
1.35x Digital	1.35x Digital	1.35x Digital	1.35x Digital	1.35x Digital
267 W	267 W	381 W	381 W	398 W
16 W	16 W	8 W x 2	8 W x 2	8 W x 2
YES	YES	YES	YES	YES
Digital	Digital	Digital	Digital	Digital
YES	YES	YES	YES	YES
–	–	–	YES	YES
–	–	–	–	–
YES	YES	YES	YES	YES
YES	YES	YES	YES	YES
YES	YES	YES	YES	YES
Manual/Manual	Manual/Manual	Manual/Manual	Manual/Manual	Manual/Manual
–	–	–	–	–
RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)
Included (802.11 a/b/g/n/ac); 5 GHz	Included (802.11 a/b/g/n/ac); 5 GHz	Included (802.11 a/b/g/n/ac); 5 GHz	Included (802.11 a/b/g/n/ac); 5 GHz	Included (802.11 a/b/g/n/ac); 2.4 GHz
Crestron, AMX, Extron, Control4, PJLink	Crestron, AMX, Extron, Control4, PJLink	Crestron, AMX, Extron, Control4, PJLink	Crestron, AMX, Extron, Control4, PJLink	Crestron, AMX, Extron, PJLink, Art-Net, Control4
HDMI x 3	HDMI x 3	HDMI x 3	HDMI x 3	HDMI x 2
VGA x 2, Composite Video	VGA x 2, Composite Video	VGA x 2, Composite Video	VGA x 2, Composite Video	–
Mini Stereo x 3	Mini Stereo x 3	Mini Stereo x 3	Mini Stereo x 3	–
Mini Stereo x 1	Mini Stereo x 1	Mini Stereo x 1	Mini Stereo x 1	–
Type-B x 2, Powered Type-A x 1	Type-B x 2, Powered Type-A x 1	Type-B x 2, Type-A x 2 (Memory Stick & Doc Camera)	Type-B x 2, Type-A x 2 (Memory Stick & Doc Camera)	USB-A x 2, Powered Type-A x 1, USB-B x 1
–	–	–	–	–
–	–	–	–	YES
–	–	HDMI Out	HDMI Out	HDMI Out
Mini D-Sub (15-Pin) x 1	Mini D-Sub (15-Pin) x 1	Mini D-Sub (15-Pin) x 1	Mini D-Sub (15-Pin) x 1	HDMI x 1
RS-232c x 1	RS-232c x 1	RS-232c x 1	RS-232c x 1	RS-232c x 1
Ultra Short Throw Wall Mount (ELPMB62)	Ultra Short Throw Wall Mount (ELPMB62)	Ultra Short Throw Wall Mount (ELPMB62)	Ultra Short Throw Wall Mount (ELPMB62)	Extreme Short Throw Wall Mount - White (ELPMB75)
100" Whiteboard (16:10)	100" Whiteboard (16:9)	100" Whiteboard (16:9)	100" Whiteboard (16:9)	Wireless LAN Adapter (ELPAP11)

^Δ5-year with product registration.

Note: Highlighted boxes indicate step-ups between models within a series.	Interactive Projectors – BrightLink Series			
	BrightLink 760Wi	BrightLink 770Fi	BrightLink 1480Fi	BrightLink 1485Fi
Interactive Features				
Pens	2 Pens Included, Dual-User Support	2 Pens Included, Dual-User Support	2 Pens Included, Dual-User Support	2 Pens Included, Dual-User Support
Pen Technology	IR, 850 nm			
Finger Touch	Optional, up to 6 Fingers	Optional, up to 6 Fingers	Optional, up to 6 Fingers	Included, up to 6 Fingers
Interactive Pen Functions	Mouse Function (Left/Right Click), Digital Pen, LED Battery Status Indicator			
PC-Free Whiteboard Sharing	YES	YES	YES	YES
DuoLink Extended Whiteboard ^o	–	–	–	YES, with Edge Blending
Calibration	Automatic or Manual			
Interactive Image Size	16:10 up to 100"	16:9 up to 100", 16:6 up to 110"	16:9 up to 100"	16:9 up to 100", 16:6 up to 120"
Interactive Connectivity	USB, Miracast, LAN	USB, Miracast, LAN	USB, Miracast, LAN	USB, Miracast, LAN
PC-Free Annotation	YES	YES	YES	YES
PC-Free Digital Whiteboard	Up to 20 Pages	Up to 20 Pages	Up to 20 Pages	Up to 20 Pages
Wall-Mounted Control Panel	–	–	–	YES
PC-Free Save, Email, Print	YES	YES	YES	YES
Android [®] OS	–	–	–	–
Gesture Support	YES, computers require Windows [®] 8/10/11 or Mac [®] OS 10 or later			
Included Software	Easy Interactive Tools for PC/Mac, Built-In Annotation Toolbar			

^oRequires Easy Interactive Driver. Certain functionality is only available through Epson Interactive Tools (EIT) software. For a list of supported operating systems, visit www.epson.com

Lens Data for Pro Series Projectors up to 8,500 Lumens (Excluding 4K Projectors)										
Epson Model	Ultra Short Throw Lens	Short Lens #1	Short Lens #2	Wide Lens #1	Wide Lens #2	Middle Lens #1	Middle Lens #2	Middle Lens #3	Middle Lens #4	Long Lens
Lens Model	ELPLX01S	ELPLU03S	ELPLU04	ELPLW05	ELPLW06	ELPLM08	ELPLM15	ELPLM10	ELPLM11	ELPLL08
Product Code	V12H004X0A	V12H004UA3	V12H004U04	V12H004W05	V12H004W06	V12H004M08	V12H004M0F	V12H004M0A	V12H004M0B	V12H004L08
Zoom Ratio	1.0x	1.0x – 1.2x	1.0x – 1.2x	1.0x – 1.4x	1.0x – 1.4x	1.0x – 1.6x	1.0x – 1.6x	1.0x – 1.5x	1.0x – 1.5x	1.0x – 1.4x
Throw Ratio (16:10)	0.35	0.65 – 0.78	0.87 – 1.05	1.04 – 1.46	1.62 – 2.22	1.42 – 2.28	2.16 – 3.48	3.32 – 5.06	4.85 – 7.38	7.21 – 10.11
White Version	V12H004Y0A	–	–	–	–	–	–	–	–	–

Lens Data for Pro Series Projectors 10,000 to 20,000 Lumens (Excluding 4K Projectors)										
Epson Model	Ultra Short Throw Lens	Short Lens #1	Short Lens #2	Wide Lens #1*	Wide Lens #2	Wide Lens #3	Middle Lens #2	Middle Lens #3	Middle Lens #4	Long Lens
Lens Model	ELPLX02S	ELPLU03S	ELPLU04	ELPLW05*	ELPLW06	ELPLW08	ELPLM15	ELPLM10	ELPLM11	ELPLL08
Product Code	V12H004X0B	V12H004UA3	V12H004U04	V12H004W05	V12H004W06	V12H004W08	V12H004M0F	V12H004M0A	V12H004M0B	V12H004L08
Zoom Ratio	1.0x	1.0x – 1.2x	1.0x – 1.2x	1.0x – 1.4x	1.0x – 1.4x	1.0x – 1.4x	1.0x – 1.6x	1.0x – 1.5x	1.0x – 1.5x	1.0x – 1.4x
Throw Ratio (16:10)	0.35	0.48 – 0.57	0.64 – 0.77	0.77 – 1.07	1.19 – 1.62	0.86 – 1.21	1.57 – 2.56	2.42 – 3.71	3.54 – 5.41	5.27 – 7.41
White Version	V12H004Y0B	–	–	–	–	–	–	–	–	–

*ELPLW05 lens has limited compatibility with 16,000-lumen and higher projectors.

Essential Teaching Tools for the Modern Classroom

Share books, 3D objects and detailed demonstrations or experiments with your entire class using Epson's easy-to-use document cameras. Record lessons for viewing at a later time and give your students a more interactive learning experience.

In addition, Epson laser displays are easy to install and easy to maintain, offering free software tools and simple, seamless integration into your tech stack.

Epson iProjection[®] App – wirelessly project from Chromebook[®], iOS[®] or Android mobile devices with the free Epson iProjection app

Epson Projector Management Connected[®] – monitor and control your networked projector fleet from any device with a Web browser tool

^a For wireless functionality, including via the Epson iProjection App, the projector must be configured on a network, either through the Ethernet port on the projector (check model specifications for availability) or via a wireless connection. Check your owner's manual to determine if a wireless LAN module must be purchased separately to enable a wireless connection. Not all Epson projectors are able to be networked. The Epson iProjection App does not support all files and formats. See www.epson.com for details.

^b Requires one on-site PC with Epson Projector Connected Agent installed.

Document Cameras				
				
Epson Model	DC-07	DC-13	DC-21	DC-30
Product Code	V12H759020	V12H757020	V12H758020	V12HB09020
Limited Warranty	2-year			
Zoom	8x Digital	16x Digital	12x Optical, 10x Digital	10x Optical, 23x Digital
Pixel Count	2MP	2MP	2MP	13MP
Output Resolution (Max.)	1080p	1080p	1080p	4K
Frame Rate	15 fps	30 fps	30 fps	60 fps
Connectivity (Output)	USB	USB, VGA, HDMI	USB, VGA, HDMI	USB, HDMI
Capture Area	10.7" x 14.3"	11.7" x 20.7"	11.7" x 20.7"	13.6" x 18.9"
A/V Recording	YES	YES	YES	YES
Built-In Microphone	YES	YES	YES	YES
Microscope Adapter	–	YES	YES	YES
SD Card Slot ^o	–	YES	YES	USB Drive Slot
Software Included	YES	YES	YES	YES

^oSD card sold separately.

Note: Highlighted boxes indicate step-ups between models within a series.

Epson Model

Product Code

Replacement Lamp Code

Previous Epson Model

Limited Warranty

Basics

Color Brightness (Color Lumens)*

White Brightness (White Lumens)*

Light Source

Light Source Life Cycle up to (Normal/Medium/Eco [Hours])†

Native Resolution**

Resolution on Screen

Ultra Wide Aspect Ratios

Weight

Dimensions (Inches)††

Dynamic Contrast Ratio (up to)

Throw Ratio

Zoom Lens (Ratio)

Power Consumption

Value-Added Features

Built-In Speaker

Closed Captioning

A/V Mute

Split Screen***

Edge Blending

Scheduling Function

Easy Connectivity and Setup

Epson iProjection™ Suite (Moderator, Multi-PC, Device Management)****

Signage Content Playback and Management Software*****

Miracast®

Quick Corner Adjustments

Screen Fit

Keystone (Horizontal/Vertical)

LAN Networking and Control

Wired

Wireless*****

Compatible Control Systems

Connections

HDMI®

Analog Connections

Audio In

Variable Audio Out

USB 2.0 Connectors

HDBaseT®

Monitor Out

Serial Control

Recommended Accessory 1

Recommended Accessory 2



LightScene® Accent Lighting Laser Projectors

LightScene laser projectors elevate ordinary spaces into stunning visual environments, unleashing dynamic, experiential content for digital art, spatial design, signage and wayfinding applications.

LightScene Projectors		
Epson Model	EV-110	EV-115
Product Code	V11HA22020	V11HA22120
Product Color	White	Black
Limited Warranty	3 Years or 20,000 Hours, Whichever Comes First	
Color Brightness (Color Lumens)*	2,200	
White Brightness (White Lumens)*	2,200	
Native Resolution	WXGA (1280 x 800)	
Contrast Ratio (Dynamic)	Up to 5,000,000:1	
Light Source Life	Up to 20,000 hours**	
Left/Right, Up/Down Movement	180 Degrees	
Ball-Joint Axis Rotation	360 Degrees	
Zoom (Powered)	1.58x	
Edge Blending Capable	YES	
HDMI/SD Card Slot***	1 x HDMI, 1 x SD Card Slot	
Variable Audio Out	1 x Stereo, Mini Out	
GPI Motion Sensor Compatible	YES	
Bluetooth® Audio	YES	
Epson Creative Content Projection App for Signage****	YES	
Epson Projector Content Manager Software****	YES	

*Color brightness (color light output) and white brightness (white light output) will vary depending on usage conditions. Color light output measured in accordance with IDMS 15.4; white light output measured in accordance with ISO 21118.

**No required maintenance for the light source for up to 20,000 hours. Approximate time until brightness decreases 50% from first usage. Measured by acceleration test assuming use of 0.04 - 0.20 mg/m³ of particulate matter. Time varies depending on usage conditions and environment. Replacement of parts other than the light source may be required in a shorter period.

***SD card sold separately.

****Internet connection required for download. Data usage fees may apply.



Epson Laser Projection Technology

As a world leader in digital 3LCD projection solutions, Epson continues to drive the future of projection technology with its full suite of laser projectors and displays. Featuring lamp-free, long-life laser light engines, Epson laser solutions achieve new levels of performance and reliability¹.

Why Choose Laser?






Breakthrough laser technology — long-life laser light engine provides up to 20,000 hours of light source life¹

Outstanding color performance and contrast — get exceptional, true-to-life color reproduction and deep, dark blacks for stunning visuals you can count on for an array of applications

Instant Off®/On — displays and projectors reach maximum brightness and turn off almost instantly, without having to warm up or cool down

Reliable operation — ideal for applications requiring extended projection

Explore Epson's Suite of Laser Projectors and Displays

				
Laser Large Venue Projectors	Interactive Laser Displays	Portable Laser Projectors	Ultra Short Throw Laser Displays	Lighting Laser Displays
High-lumen laser projectors designed for exceptional performance in large venues	Full HD, ultra short throw interactive laser displays for collaborative meetings and learning	High-performance laser projectors offering a variety of brightness, connectivity and resolutions	Bold, rich, Full HD laser displays for virtually any application, including those in small spaces, without any shadows	Project dynamic, experiential content for digital art, commercial signage and décor applications

Epson PreferredSM Plus Extended Service Plans[◇]

We've got you covered.

Epson Preferred Plus Extended Service Plans offer you peace of mind with a variety of flexible plan options to best fit your needs and budget, helping you maximize uptime and protect your investment.



For more information, go to www.epson.com/esp

For Brighter Futures[®] Extended Service Plans see, www.epson.com/brighterfutures

Extended Service Plans[◇]

- PowerLite E, X, W, U, 100, 900, 1200, 1700 Series, PowerLite 685W, 1-Year Next-Business-Day Whole Unit Exchange (Years 3-5)⁹⁰ EPPPEXA1
- PowerLite E, X, W, U, 100, 900, 1200, 1700 Series, PowerLite 685W, 2-Year Next-Business-Day Whole Unit Exchange (Years 3-5)⁹⁰ EPPPEXA2
- PowerLite E, X, W, U, 100, 900, 1200, 1700 Series, PowerLite 685W, 3-Year Next-Business-Day Whole Unit Exchange (Years 3-5)⁹⁰ EPPPEXA3
- PowerLite Series Model 2250U, 1-Year Next-Business-Day Whole Unit Exchange (Years 3-5)⁹⁰ EPPPEXPB1
- PowerLite Series Model 2250U, 2-Year Next-Business-Day Whole Unit Exchange (Years 3-5)⁹⁰ EPPPEXPB2
- PowerLite Series Model 2250U, 3-Year Next-Business-Day Whole Unit Exchange (Years 3-5)⁹⁰ EPPPEXPB3
- EB-PU1000/2000, 1-Year Next-Business-Day Whole Unit Exchange (Year 4 or 5) EPPPEXPC1
- EB-PU1000/2000, 2-Year Next-Business-Day Whole Unit Exchange (Years 4-5) EPPPEXPC2
- Pro L30000 Series, 1-Year Return for Repair Extension (Year 4 or 5) EPPPEXPD1
- Pro L30000 Series, 2-Year Return for Repair Extension (Years 4-5) EPPPEXPD2
- PowerLite L Series, LightScene Series, 1-Year Next-Business-Day Whole Unit Exchange (Year 4 or 5) EPPPEXPE1
- PowerLite L Series, LightScene Series, 2-Year Next-Business-Day Whole Unit Exchange (Years 4-5) EPPPEXPE2
- BrightLink, PowerLite 700 and 800 Series, 1-Year Next-Business-Day Whole Unit Exchange (Year 4 or 5) EPPPEXPF1
- BrightLink, PowerLite 700 and 800 Series, 2-Year Next-Business-Day Whole Unit Exchange (Years 4-5) EPPPEXPF2
- DC-07, 1-Year Next-Business-Day Whole Unit Exchange EPPDCAE1
- DC-07, 3-Year Next-Business-Day Whole Unit Exchange EPPDCAE3
- DC-13, DC-21, 1-Year Next-Business-Day Whole Unit Exchange EPPDCBE1
- DC-13, DC-21, 3-Year Next-Business-Day Whole Unit Exchange EPPDCBE3
- DC-30, 1-Year Next-Business-Day Whole Unit Exchange EPPDCE1
- DC-30, 3-Year Next-Business-Day Whole Unit Exchange EPPDCE3
- EB-PU2100/2200, 3-Year Shipping Upgrade to Next-Business-Day (Years 1-3) EPPPRJPU3
- EB-PU2113W, EB-PU2116W, EB-PU2213B, EB-PU2216B, 5-Year Next-Business-Day Upgrade (Years 1-3) and Extension (Years 4-5) EPPPRJPUE5
- EB-PU2120W, EB-PU2220B, 5-Year Next-Business-Day Upgrade (Years 1-3) and Extension (Years 4-5) EPPPRJPU20E5
- EB-PQ Series, 3-Year Shipping Upgrade to Next-Business-Day (Years 1-3) EPPPRJPQ3
- EB-PQ Series (Except EB-PQ2220B), 5-Year Next-Business-Day Upgrade (Years 1-3) and Extension (Years 4-5) EPPPRJPQE5
- EB-PQ2220B, 5-Year Next-Business-Day Upgrade (Years 1-3) and Extension (Years 4-5) EPPPRJPQ20E5

[◇]Check individual extended service plans for Terms and Conditions. Coverage varies by plan. Expedited shipping not available in all areas. Orders must be placed and processed by 1 p.m. Pacific Time, Monday through Friday, excluding holidays. See limited warranty or service plan for details. Pro L30000 Series not eligible for Next-Business-Day replacement. 1 [◇]Lamp-based models only.

Epson America, Inc.
3131 Katella Ave., Los Alamitos, CA 90720

Epson Canada Limited
185 Renfrew Drive, Markham, Ontario L3R 6G3

www.epson.com
www.epson.com/projectors

www.epson.ca

¹ No required maintenance for the light source for up to 20,000 hours. Approximate time until brightness decreases 50% from first usage. Measured by acceleration test assuming use of 0.04 - 0.20 mg/m³ of particulate matter. Time varies depending on usage conditions and environment. Replacement of parts other than the light source may be required in a shorter period. Large Venue Series: 20,000 hours is the estimated life when the projector is used in Normal Mode in an ordinary environment. Actual hours may vary depending on mode and usage environment. The projector has a limited warranty of 3 years or 20,000 hours, whichever comes first. The EB-PU Series and EB-PQ Series of projectors have a standard limited warranty of 3 years. Interactive, Digital Signage and Accent Lighting Projectors: 20,000 hours is the estimated projector life when used in Normal Mode. Actual hours may vary depending on mode and usage environment. Interactive and Digital Signage Projectors come with a 3-year limited warranty; Accent Lighting Projectors have a limited warranty of 3 years or 20,000 hours, whichever comes first. Corporate Series: 20,000 hours is the estimated laser light source life when used in Normal Mode. Actual hours may vary depending on mode and usage environment. The projector has a standard limited warranty of 3 years.

Specifications and terms are subject to change without notice. EPSON, Instant Off, LightScene and PowerLite are registered trademarks and Epson iProjection is a trademark of Seiko Epson Corporation. BrightLink and Brighter Futures are registered trademarks, Epson Preferred, Pilot and PixAlign are trademarks of Epson America, Inc. Mac is a trademark of Apple Inc., registered in the U.S. and other countries. Android and Chromebook are registered trademarks of Google LLC. Windows is a trademark of the Microsoft group of companies. Miracast[®] is a registered trademark and Wi-Fi CERTIFIED™ is a trademark of Wi-Fi Alliance[®]. All other product and brand names are trademarks and/or registered trademarks of their respective companies. Epson disclaims any and all rights in these marks. Copyright 2024 Epson America, Inc. CPD-63281R1 3/24